



Folding Wall Systems

Offices, schools, universities, leisure & sport centres

Our Folding Wall System is a hinged panel system providing sound reduction from 25dB to 48dB.

Supplied as either a top hung or floor supported system. The floor supported option features a low profile threshold which is designed to address trip hazard concerns.

Single or double wing available with access gained via the hinged panel in the last leaf of each wing. Easy operation of the screen is achieved by the use of high specification rollers and track. An adjustable hinged jamb allows unrivalled system adjustment yet still allows a concealed wall fixing.

Sound performance is achieved by specialised manufacturing techniques including high specification acoustic infill.

Available in a range of finishes including laminate, white marker, veneer, digi-art or primed for onsite decorating.

All hardware is finished in hardwearing, compliant natural anodised aluminium or optional stainless steel.

Technical Specifications

Nominal thickness	70 mm / 100 mm
Max. panel width:	850 mm
Centre hung	700 mm
End hung:	
Max. clear opening height	3600 mm
Approx. hanging weight	22 – 47 kg/m ²
Sound insulation range	25 – 48 dB

- Acoustically rated 25db – 48db
- Vast selection of finishes – including veneer, laminate, melamine etc.
- Single wing or Bi parting stacking
- Can be top hung or floor supported
- Supplied as standard with full height pass door