



## Movable Wall Systems

Acoustically divide conference/seminar rooms, class rooms, function rooms, office space & community halls

The Movable Wall System is truly at the top of the product range. UK manufactured, this top hung system allows limitless stacking solutions.

Acoustic infill combined with interlocking edge profiles with interlocking seal interfaces giving up to 59dB sound block performance.

Seal pressure of up to 2KN per linear metre is made possible by the rapid action scissor jack mechanism ensuring excellent onsite acoustic performance can be achieved.

The mechanism also performs within site restrictions or constraints such as uneven floors and deflections. Magnetic profiles complement precision engineered roller and track systems allowing effortless operation. Roller locking mechanisms guarantees panel alignment in the long term.

All systems are acoustically tested and certified.

Available in a range of finishes including laminate, white marker, veneer, digi-art or primed for onsite decorating.

### Technical Specification

Normal thickness	100mm
Min. panel width	650mm
Max. panel width	1250mm
Max. clear opening height	11m
Sound insulation range	Up to 59dB

- High acoustic performance up to 59db
- Acoustically tested pass doors
- Vast selection of finishes – including veneer, laminate etc.
- Flexible division with various stacking options
- Top hung with no floor tracks
- Fire rated options available
- Panels can be manufactured up to 11m high
- Semi-automatic system available, call for further information